SABIN

STADIA

DATE	PROJECT	FIRM	FIXTURE TYPE
DAIL	THOSEOT	1 11 11 11	TIXTONETTIE



STADIA 27 - UNLIT ONLY

Stadia 27 is clean, cost conscious and acoustically effective. Our commitment to craft shows up in Sabin's signature sewn construction, which enables a robust and simple design. Sabin's family of linear products share a common design language. These products are intended to work together as part of larger arrays, selected according to lighting, acoustic and budgetary requirements.

SPECIFICATIONS

SERIES	STYLE	LENGTH ¹ HEIGHT ¹	FELT COLOR
L-27	SCL CLASSIC SFL FLUTED	26" (653MM) 8" (200MM) 38" (953MM) 11" (285MM) 49" (1253MM) 16" (400MM) 61" (1553MM) 20" (500MM) 74" (1878MM) 23" (585MM) 86" (2178MM) 47" (1200MM) 92" (2328MM) CH4	9BSBISQUE9OBOBSIDIAN9BRBIRCH9PNPINE9CNCANARY9PMPUMICE9FLFLINT9QYQUARRY9GFGULF9SDSAND9HZHAZEL9SPSAPPHIRE9JDJADE9SASIENNA9MSMOSS9WSWISTERIA
TRIM COLOR (O	PTIONAL PREMIUM FINISH)	MOUNTING	FACTORY OPTIONS ⁶
NO TRIMAZAZUREBFBLUFFCYCLAYCTCITRUSCUCURRANTDUDUNEEMEMERALDFEFERN	FR FROST SH SHELL HI HIBISCUS SK SKY IN INDIGO SL SLATE IR IRIS SP SPRUCE LM LIME ST STONE OL OLIVE TM TIMBER OX ONYX WH WHITE PO POPPY SG SAGE	AC60° AIRCRAFT CABLE + (COLOR CODE) 5 WEB60° WEBBING + (COLOR CODE) 5 TRD 3/8" THREADED ROD DTS DIRECT TO STRUT DTG DIRECT TO GRID	CSL CUSTOM SUSPENSION LENGTH 24"-120" 7 CT CUSTOM THREAD 8 2CP INCLUDE 2" CANOPIES

1 IMPERIAL DIMENSIONS ARE NOMINAL. ACTUAL DIMENSIONS ARE METRIC. 2 CUSTOM LENGTHS AVAILABLE BETWEEN 24" - 95" (600-2420MM).

REPLACE " " WITH LENGTH OF DESIRED SUSPENSION.

8 CONSULT FACTORY FOR CUSTOM THREAD COLOR OPTIONS

SEE ADDITIONAL OPTIONS FOR SIZE, TRIM FINISH, AND CUSTOMIZATION AT SABIN.BUILD



EXAMPLE PART NUMBER: L-27-SCL-49(1253)-11(285)-9JD-TM-ACSLV





LINEAR

STADIA

DATE	PROJECT	FIRM	FIXTURE TYPE

SWATCHES

SABIN

Stadia utilizes 9mm felt and has the option to customize color for cable and thread — and cord (for lit fixtures.)

Contact the factory for additional color options.


9MM FELT



TRIM (OPTIONAL PREMIUM FINISH)



CABLE





SPRUCE - SP STONE - ST Living Building Challenge Cri

IRIS - IR

Colors are subject to slight variation from your screen or paper to the finished product.

SHELL - SH

SKY-SK

SLATE - SL





sed: 100% at 100ppm

are.

ec PET Acoustic Felt Sabin LLC

POPPY - PO

DATE REVISED 02.14.2024

HIBISCUS - HI

INDIGO - IN

SABIN





DATE

PROJECT

FIRM

FIXTURE TYPE

ACOUSTIC PERFORMANCE DATA

ALL SABIN PRODUCTS ARE SUBJECT TO ACOUSTIC TESTING. PERFORMANCE VALUES WILL VARY BASED ON INSTALLATION FACTORS SUCH AS DENSITY AND MOUNTING HEIGHT.

- A SABIN IS A UNIT OF SOUND ABSORPTION DEFINED AS THE AMOUNT OF SABINS SOUND ABSORBED BY ONE SQUARE FOOT OF A PERFECT ABSORBER. IT WAS INITIALLY CONCEIVED AS THE EQUIVALENT OF 1 SQUARE FOOT OF OPEN WINDOW, REFLECTING NO SOUND BACK INTO THE INTERIOR. SABINS ARE USED TO EXPRESS THE TOTAL EFFECTIVE ABSORPTION FOR THE INTERIOR OF A ROOM. THIS CHART INDICATES AVERAGE SABINS PER UNIT AT THE NOTED FREQUENCIES WHICH REPRESENT THE TYPICAL RANGE OF HUMAN SPEECH OF 200-2500 HZ.
- NOISE REDUCTION COFFEICIENT (NRC) IS A SINGLE NUMBER VALUE NRC RANGING FROM 0.0 TO 1.0 THAT DESCRIBES THE AVERAGE SOUND ABSORPTION PERFORMANCE OF A MATERIAL. AN NRC OF 0.0 INDICATES THE OBJECT DOES NOT ABSORB MID-FREQUENCY SOUND ENERGY, BUT REFLECTS IT. AN NRC OF 1.0 INDICATES THAT THE SOUND ABSORPTION PERFORMANCE OF THE MATERIAL IS EQUAL TO ITS SURFACE AREA (MEASURED IN UNITS SABIN), OR CONCEPTUALLY 100% SOUND ABSORPTION.

PROJECTED NRC = .95

TOTAL SOUND ABSORPTION WILL VARY BASED ON DESIGNED PRODUCT CONFIGURATION SABIN TESTS ALL PRODUCTS IN MULTIPLE CONFIGURATIONS. PLEASE CONTACT SABIN OR YOUR LOCAL AGENT FOR MORE INFORMATION.

DIMENSIONS + WEIGHT

SERIES	LENGTH ^{1,4}	HEIGHT ¹	WIDTH ¹
L-27	26" (653MM) 38" (953MM) 49" (1253MM) 61" (1553MM) 74" (1878MM) 86" (2178MM) 92" (2328MM) CL ² CR ⁵	6" (150MM) 7" (185MM) 11" (285MM) 16" (400MM) 20" (500MM) 23" (585MM) CH ³	1" (27MM)

1 IMPERIAL DIMENSIONS ARE NOMINAL. ACTUAL DIMENSIONS ARE METRIC. 2 CUSTOM LENGTHS AVAILABLE BETWEEN 24" - 95" (600-2420MM).

3 CUSTOM HEIGHTS AVAILABLE BETWEEN 6" - 23" (150-585MM)


4 FLINT AND PUMICE LENGTHS CAN BE SPECIFIED UP TO 2880MM


* ALL STANDARD DIMENSIONS ARE ECO-CONSCIOUS, MAXIMIZING MATERIAL USE AND MINIMIZING WASTE. CUSTOM DIMENSIONS RESULT IN EXCESS MATERIAL WASTE.

WEIGHT

PLEASE CONSULT THE FACTORY FOR PRODUCT WEIGHTS BASED ON CONFIGURATION AND PART NUMBERS.

SABIN LINEAR FAMILY PROJECTED PERFORMANCE





See Dimensions and Weight Table for Limitations

© 2023 SABIN LLC. ALL RIGHTS RESERVED. SABIN AND THE SABIN LOGO ARE REGISTERED TRADEMARKS OF SABIN LLC.





SABIN

LINEAR

STADIA

DATE

PROJECT

FIRM

FIXTURE TYPE

ACOUSTIC MATERIAL

OUR 9MM PET (POLYESTER) FELT PANELS CONTAIN MINIMUM 60% POST-CONSUMER RECYCLED POLYESTER STAPLE FIBER. THE MATERIAL IS MOISTURE RESISTANT, FIRE RATED AND RECYCLABLE. THE POROUS MATERIAL IS AN OUTSTANDING ABSORBER OF ACOUSTIC ENERGY.

FIRE RETARDANT: ASTEM E84 CLASS A , EN13501 CLASS B
DECORATIVE: 11 STANDARD COLORS

· CONSTRUCTION: 100% POLYESTER FIBER (PET)

CONSTRUCTION

A 9MM PET PANEL FOLDED AND SEWN AROUND A RIGID ALUMINUM EXTRUSION, WITH INTEGRATED REPOSITIONABLE SUSPENSION SYSTEM. THIS PATENT PENDING DESIGN EASY TO INSTALL AND SIMPLE TO ADJUST.

MOUNTING

SUSPENDED WITH 1/16" (1.6MM) AIRCRAFT CABLES, COLOR MATCHING CABLE AND GRIPPERS, INSTALLED AT FACTORY, AIRCRAFT CABLES AVAILABLE IN PRECUT LENGTHS OF 36" (915MM), 60" (1524MM), OR 120" (3048MM) WITH FABRIC-COVERED POWER CORD AND 5" (125MM) CANOPY.

CERTIFICATES/LISTING

TESTED IN ACCORDANCE WITH NEC, ANSI/NFPA 70 STANDARDS. SUITABLE FOR INDOOR, DRY-LOCATION USE ONLY, IP20.

CARE

PET ACOUSTICS: REMOVE DUST WITH COMPRESSED AIR, A VACUUM OR LINT ROLLER. ALUMINUM & POLYMER COMPONENTS: REMOVE DUST AND DEBRIS WITH A CLEAN, DRY, OR DAMP LINT-FREE CLOTH.



MANUFACTURED EQUIPMENT IS WARRANTED TO BE FREE OF DEFECTS AND FAILURE UNDER NORMAL USE AND PROPER STORAGE FOR A PERIOD OF FIVE (5) YEARS.



Δ